



Mobile push camera VT 15 NC

Camera system for pipes between 15 - 125 mm with battery operation

Applications/Features

Applications

- Pipe inspections
- Shaft inspections
- Borehole inspections
- All inspections in domestic environments
- Inspections in hard to reach areas

Features

- Mobile operation with battery backup
- Various camera heads available, optional automatic horizontal positioning (upright image)
- Integrated recorder with color monitor for video recording and screenshots
- Various push rods available
- Integrated centering
- Water-tight up to 5 bar (depending on the camera head)

Technical specifications

VT NC 15

Reel material	Carbon / stainless steel
Glass fiber push cable	30m/Ø 5,6mm / 40m/Ø 5,6mm or standard push cable 30m/ Ø5 mm
Power supply	100-240 Volt, 12V DC charger input, battery
Image sensor	CCD color sensor
Video out	FBAS (BNC)
Resolution	560 lines hor.
Sensitivity	0.02 Lux at f=1.2
Diameter camera	KK13 13mm / KK18 18mm
Focus	fixed focus
Lighting	LED
Dimensions	230 x 395 x 350 mm (L x W x H)
Weight	approx. 6 kg
Operating temperature	0 – 50°
Water tight	up to 5 bar
Meter counter	integrated
Monitor	5,6" Color Monitor
Recorder	Recording to SD-Card using mpeg4-Format (Video) Still shot-Function (640 x 480 Pixel)

Accessories

Centering	various sizes available
Tracking help	optional